

Model T2 Specifications

BATTERY-POWERED WALK-BEHIND SCRUBBER-DRYER

Feature		
Scrubbing System		
Cleaning Path		43 cm/ 17 in. – Pad Assist
Solution Tank Capacity		26 liter / 6.9 gal.
Productivity (Per Hour) Theoretical Max Estimated Actual		 1,900 m^2 / 20,230 ft^2 672 m^2 / 7,234 ft^2
Variable Solution Flow Rate		0-1.1lpm / 0-.3 gpm
Brush Motor		.75 kW / 1 hp
Brush Operating Speed		230 rpm
Maximum Brush / Pad Pressure		23 kg / 50 lbs.
Recovery System		
Recovery Tank Capacity		36 liter/ 9.5 gal. – fully accessible and cleanable (Includes demisting chamber)
Vacuum Fan Motor Stages Vacuum Motor (Maximum) Sealed Water Lift		 0.30 kW/ 0.4 hp 2 1.84 cubic mm/minute / 65cfm 102 cm / 40 in.
Squeegee Description		69.5 cm/ 27.4 in. curved squeegee assembly with quick-change four sided rear blade
Drive System		
Caster Description		70 mm/ 2.75 in. diameter polyurethane
Wheel Description		178 x 38 mm/ 7 in. x 1.5 in. non-marking polyurethane
Batteries (12V system) Optional Lead Acid / Run time Optional Gel / Run time Optional Lead Acid/Run time		 (2) 12V, 85 AH / Up to 2 hours (4) 12V, 70 AH / Up to 1.75 hours (2) 12V, 72 AH / Up to 1.75 hours (EU Only)
Dimensions / Weight / Sound level		
Length		112 cm / 44.1 in.
Width Body Scrub head Squeegee		 44.1 cm / 17.4 in. 47.8 cm / 18.8 in. 69.5 cm / 27.4 in.
Height Maximum (Handle Lowest Position)		93 cm / 36.6 in.
Height Adjustable Handle - Range		12.6 cm / 5 in.
Net Weight Less Batteries With Batteries (2) 12V 70 AH gel		 80 kg / 176 lbs. 136 kg / 300 lbs.
Minimum Aisle Turn:		122 cm/ 48 in.
Sound Level		68 dBa
Warranty	24 months (or max 2000 running hours) on parts and 12 months (or max 1000 running hours) on labour, which ever comes first, excluding wear items	