T300 | Walk-Behind Scrubber-Dryer

Product Specifications

Feature	430 mm Single Disk Pad Assist	430 mm Single Disk Self Propel	500 mm Single Disk Pad Assist	500 mm Single Disk Self Propel	600 mm Dual Disk Self Propel	500 mm Dual Cylindrical Self Propel	500 mm Orbital Self Propel
Control Panel	Membrane™ Panel (Std) Pro-Panel™ (Optional)	Membrane™ Panel (Std) Pro-Panel™ (Optional)	Membrane™ Panel (Std) Pro-Panel™ (Optional)	Membrane™ Panel (Std) Pro-Panel™ (Optional)	Membrane™ Panel (Std) Pro-Panel™ (Optional)	Membrane Panel (Std) Pro-Panel™ (Optional)	Membrane™ Panel (Std) Pro-Panel™ (Optional)
Cleaning Tool Attachment	Insta-Click™					N/A	N/A
Drive Motor	N/A	0,23 HP / 0,175 kW	N/A	0,23 HP / 0,175 kW			
Machine Speed	Scrub Speed: 3,66 Km/h Transport: 4,38 Km/h Reverse: 2,64 Km/h						
Scrubbing Coverage Rate (m²/hr) Theoretical Max Conventional ec-H2O NanoClean™	 1.579 m² 868 m² 898 m²	 1.579 m² 1.157 m² 1.198 m²	 1.858 m² 1.041 m² 1.078 m²	 1.858 m² 1.388 m² 1.437 m²	 2.230 m² 1.697 m² 1.756 m²	 1.858 m² 1.388 m² 1.437 m²	 1.858 m² 1.388 m² 1.437 m²
Brush/Pad Drive System							
Cleaning Path	430 mm		500 mm		600 mm	500 mm	500 mm
Scrub Motor	24 VDC, 1 HP / 0,75 kW						0,45 kW / 0,6 HP
Brush/Pad RPM	230 rpm				285 rpm	1.065 rpm	2.200 rpm
Brush/Pad Down Pressure	21, 32, 39 kg		23, 35, 41 kg		26, 37, 44 kg	24, 27, 29 kg	29, 42, 49 kg
Solution and Recovery Systems							
Solution Tank Capacity	42 l						
Recovery Tank Capacity	53 l						
Vacuum Motor	24 VDC, 0,6 HP / 0,47 kW						
Vacuum Water Lift	1.067 mm						
Vacuum Water Lift With Quiet Mode™	711 mm						
Cleaning Technology							
Conventional	Standard						
Conventional Water Flow	Low: 0,57 lpm Med: 1,3 lpm High: 1,9 lpm						
ec-H2O NanoClean™ Technology	Optional						
ec-H2O NanoClean™ Technology Water Flow	Low: 0,45 lpm Med: 0,94 lpm High: 1,3 lpm						
Severe Environment	Optional with ec-H2O NanoClean™						
Severe Environment™ detergent Tank Capacity	1,5 L Optional only with ec-H20 NanoClean™						

©2015 The Tennant Company

Tennant Company
701 North Lilac Drive, Minneapolis, MN 55422 USA
+1.800.553.8033 | www.tennantco.com | info@tennantco.com

T300 | Walk-Behind Scrubber-Dryer

Product Specifications

Feature	430 mm Single Disk Pad Assist	430 mm Single Disk Self Propel	500 mm Single Disk Pad Assist	500 mm Single Disk Self Propel	600 mm Dual Disk Self Propel	500 mm Dual Cylindrical Self Propel	500 mm Orbital Self Propel
Battery System							
System Voltage	24 Volts						
Battery Count	2						
Batteries	Wet 120AH with Battery Fill System Sealed Gel 76AH Sealed Gel 105AH Sealed Gel Fast Charge 60AH						
Battery Run Time (Up to Hours)	3,0	2,8	2,5	2,4	2,2	1,9	3,1
Onboard Charger	Optional						
OffBoard Charger	Optional						
Decibel Ratings							
Sound Level At Operator Ear (dBA)	64,9	64,9	64,9	64,9	66,5	65,6	66,4
Quiet Mode™ At Operator Ear (dBA)	57,8	57,8	57,8	57,8	59,1	TBD	57,6
Machine Dimensions and Weights							
Squeegee Width	772 mm						
Length X Widith X Height	1302 x 500 x 1095 mm		1372 x 559 x 1095 mm		1314 x 660 x 1095 mm	1283 x 635 x 1095 mm	1245 x 521 x 1095 mm
Weight (less batteries)	98 kg	104 kg	104 kg	109 kg	113 kg	113 kg	216 kg
Weight (with batteries)	166 kg	177 kg	171 kg	181 kg	186 kg	186 kg	188 kg

©2015 The Tennant Company

Tennant Company
701 North Lilac Drive, Minneapolis, MN 55422 USA
+1.800.553.8033 | www.tennantco.com | info@tennantco.com